



## TECHNICAL INFORMATION TIMBERTREAT ONE COAT Timber Finish

### APPLICATIONS:

- Decking, verandahs
- Outdoor furniture
- Fencing, lattice, battens
- Park tables and benches
- Gazebos, pergolas, shingles
- Posts, guide posts, signs
- Decorative timber panels
- Floor boards, house timbers
- Timber louvers and shutters
- Hand rails

### BENEFITS:

- Protects timber by penetrating the surface, inhibiting moisture loss or gain.
- This combination inhibits deterioration of the timber by reducing moisture ingress.
- TimberTreat One Coat will not crack, flake or peel.
- Easy to apply with brush, spray or lambs wool applicator.
- Available in Natural and five timber colours. Honey, Cedar, Jarrah, Ironbark & Teak.
- All of the colours are water based, and only require a single application on most materials. Natural is a clear finish, whilst the rest contain a transparent tint which does not hide the grain of the timber.

### PREPARATION:

- TimberTreat One Coat needs to ingress into the timber to be effective. Some timbers are so full of water or oils that adequate ingress is not possible. In these cases a re-application of TimberTreat after 3 to 6 months is recommended. Slow drying or resinous timbers include Kwila, Merbau, Balau, Cypress Pine, Brushbox, Spotted Gum, Tallowood, green hardwoods and green treated pine. Use seasoned timber (air or kiln dried) wherever possible.
- Any material blocking that ingress must be removed from the timber.
- On previously oiled timber, clean the surface using Cooee Timber Cleaner. Rinse well with water and let dry thoroughly.
- On previously painted or varnished surfaces remove the old coating by thoroughly sanding to bare timber.



**APPLICATION METHOD:**

1. Thoroughly SHAKE & STIR before and during application.
2. For best results apply evenly along the grain. Apply **generously** to all surfaces. If any material is still not absorbed into the surface after 15-20 minutes, spread out the excess and allow to dry. Alternatively, if the coating is absorbed in 1-2 minutes, the timber is porous, and a second coat is advisable.
3. On non-porous surfaces, such as bamboo, do NOT apply too thick, as it will remain sticky for a long time, and may take several days to cure.
4. Touch dry in 2 hours – fully cured in 48 hours.
5. A second coat of TimberTreat is normally not required. If the timber is porous, such as old dry wood, or dry treated pine, a second coat will add extra protection and give longer life to the coating. The first coat should be dry before applying the second coat. The extra coat will deepen the colour of the coating.
6. Typical **application rates** for softwood and hardwood are approximately 1 litre to 8-10 square metres. Rates can vary greatly depending on the type and condition of the timber. Older timber may require an extra coat.
7. Apply with brush, spray, lambs wool applicator or roller.
8. Clean up with warm, soapy water.
9. Drying and curing times are set at 25 degrees and 50 percent humidity. Lower temperatures and higher humidity will lengthen these times.

**MAINTENANCE:**

1. To add further applications over time, simply clean and apply – no sanding is necessary.
2. A reapplication is necessary only when there is a noticeable absorption of moisture into the timber. TimberTreat One Coat is all that is needed for subsequent reapplications.
3. Frequency of re-coating(s) will vary depending on factors such as condition of the timber, degree of exposure, traffic volumes etc.
4. Please keep out of the reach of children.

