



TECHNICAL INFORMATION TIMBERTREAT TINTED Timber Finish

APPLICATIONS:

- Decking, verandahs
- Outdoor furniture
- Fencing, lattice, battens
- Park tables and benches
- Gazebos, pergolas, shingles
- Posts, guide posts, signs
- Weatherboards
- Bridges, jetties, boardwalks
- Decorative timber panels
- Landscape edging, railway
- Floor boards, house timbers
- Sleepers
- Timber louvers and shutters
- Hand rails

BENEFITS:

- Protects timber by penetrating the surface, inhibiting moisture loss or gain.
- This combination inhibits deterioration of the timber by reducing moisture ingress.
- TimberTreat Tinted Timber Finish will not crack, flake or peel.
- Easy to apply with brush, spray or lambs wool applicator.
- Available in four timber colours. Cedar, Jarrah, Ironbark and Teak.

PREPARATION:

- TimberTreat Tinted Timber Finish needs to ingress into the timber to be effective. Some timbers are so full of water or oils that satisfactory ingress is not possible. In these cases a reapplication of TimberTreat Tinted Timber Finish after 4 to 6 months will give improved protection. Slow drying or resinous timbers include Kwila, Merbau, Balau, Cypress Pine, Brushbox, Spotted Gum, Tallowood, green hardwoods and green treated pine. Use seasoned timber (air or kiln dried) wherever possible. If timber can be left to the weather before coating, this should open the grain of the timber, and allow more of the finish to ingress, thus offering increased protection.
- Any material blocking that ingress must be removed from the timber.
- On previously painted or varnished surfaces remove the old coating by thoroughly sanding to bare timber. Clean the surface with warm soapy water, rinse off and allow to dry.

TimberTreat - Tinted



APPLICATION METHOD:

1. Thoroughly SHAKE & STIR before and during application.
2. For best results apply evenly along the grain. **Two coats** are necessary.
3. Touch dry in 2 hours – fully cured in 48 hours.
4. Typical **application rates** for softwood and hardwood are approximately 1 litre to 10 square metres. Rates can vary greatly depending on the type and condition of the timber. Older timber may require an extra coat.
5. Apply with brush, spray or lambs wool applicator. Roller not recommended unless tipped off with a brush immediately.
6. Clean up with turpentine.

MAINTENANCE:

1. To add further applications over time, simply clean and apply – no sanding is necessary.
2. A reapplication is necessary only when there is a noticeable absorption of moisture into the timber, or as colours fade. TimberTreat Tinted Timber Finish is all that is needed for subsequent reapplications.
3. Frequency of re-coating(s) will vary depending on factors such as condition of the timber, degree of exposure, traffic volumes etc.
4. Protected areas retain their appearance and effectiveness longer than the more exposed areas.
5. Please keep out of the reach of children.

TimberTreat - Tinted



COOEE PRODUCTS Pty Ltd. ABN 12 107 219 956. Quality Assured to ISO 9001:2000.

30 Fishermans Road Maroochydore QLD 4558 AUST. PO Box 5993 MAROOCHYDORE B.C. QLD 4558 AUST.
Ph: 07 54 79 1620 Fax: 07 54 79 1602 w: www.cooeeproducts.com.au e: info@cooeeproducts.com.au